## NSN 4820-00-373-8130

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-373-8130 **Thread Class:** 3b all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Valve Discharge Flow Rate:** 6.0 gallons per minute **Maximum Operating Temp:** 110.0 degrees fahrenheit single response **Connection Style:** Gasket sea (boss) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss all ends **Features Provided:** Pressure tight outlet side **Maximum Operating Pressure:** 2625.0 pounds per square inch single response **Thread Size:** 0.750 inches all ends **Opening Pressure Setting:** 2625.0 pounds per square inch Material: Stainless steel seat Media For Which Designed: Hydraulic fluid, phosphate-ester base single response **Surface Treatment:** Anodize **Style Designator:** Straight through note: to be used for valve bodies of separable sections. **Thread Series Designator:** Unf all ends Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 4820-00-373-8130

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0