NSN 4820-00-375-7262

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-375-7262

Pipe Size Accommodated:				
0.125 inches 1st end				
Thread Direction:				
Right-hand 1st end				
Flow Control Device:				
Poppet				
Disk Loading Method:				
Spring				
Maximum Operating Temp:				
250.0 degrees fahrenheit 2nd response				
Connection Style:				
Plain (pipe) 1st end				
Valve Operation Method:				
Automatic				
Connection Type:				
Threaded external pipe 1st end				
Thready Qty Per Inch (tpi):				
27 1st end				
Maximum Operating Pressure:				
200.0 pounds per square inch single response				
Thread Size:				
0.125 inches 1st end				
Opening Pressure Setting:				
4.0 pounds per square inch				
Special Features:				
Pop-off type				
Material:				
Aluminum alloy 2024 body				
Material Specification:				
Qq-a-225/6, alloy2024, t4 federal specification 1st material response flow control device				
Media For Which Designed:				
Hydrogen 5th response				
Surface Treatment:				
Anodize				
Surface Treatment Specification:				
Mil-a-8625, type 1 military specification single treatment response				
Style Designator:				
Straight through note: to be used for valve bodies of one section only.				
Thread Series Designator:				
Npt 1st end				
Shelf Life:				
N/a				

NSN 4820-00-375-7262

Safety Relief Valve - Page 2 of 2



ι	Jnit	Of	Measure:
•	,,,,,	•	moudai c.

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.