

View Online at <https://aerobasegroup.com/nsn/4820-00-375-7999>

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Threaded

Renewable Seat Ring Type:

Threaded

Valve Operation Method:

Manual

Flange Shape:

Round 2nd end

Connection Type:

Flange 1st end

Features Provided:

Bonnet packing

Valve Size:

0.750 inches

Maximum Operating Pressure:

350.0 pounds per square inch single response

Outside Diameter:

4.313 inches 1st end

Thickness:

0.688 inches 2nd end

First Connection Face To Centerline Distance:

4.125 inches

Second Connection Face To Centerline Distance:

3.500 inches

Flange Face Design:

Plain 2nd end

Raised Face Height:

1.875 inches 1st end

Material:

Nickel alloy 400 stem

Style Designator:

Angle flanged ends

Test Data Document:

80064-ss-s4824-935001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Specification Or Standard:

A assembly

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0