## NSN 4820-00-383-7918

Globe Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-383-7918

| view Online at https://aerobasegroup.com/nsn/4820-00 |
|--|
| Thread Direction:                                    |
| Right-hand 1st end                                   |
| Flow Control Device:                                 |
| Stem or disk   |
| Bonnet Type:   |
| Inside screw   |
| Bonnet Attachment Method:                            |
| Threaded   |
| Maximum Operating Temp:                              |
| 225.0 degrees fahrenheit single response             |
| Connection Style:                                    |
| Plain (pipe) 1st end                                 |
| Valve Operation Method:                              |
| Manual   |
| Connection Type:                                     |
| Threaded external pipe 1st end                       |
| Features Provided:                                   |
| Bonnet packing                                       |
| Maximum Operating Pressure:                          |
| 6000.0 pounds per square inch single response        |
| Thread Size:   |
| 0.250 inches 1st end                                 |
| Material:  |
| Steel comp 316 stem                                  |
| Media For Which Designed:                            |
| Water-oil-gas single response                        |
| Style Designator:                                    |
| Straight thru  |
| Thread Series Designator:                            |
| Npt 1st end  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:                                     |
|  |
| Demilitarization:                                    |
| No   |
| Fiig:  |
| A046b0   |
|  |
|  |