

View Online at <https://aerobasegroup.com/nsn/4820-00-388-9936>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

150.0 degrees fahrenheit 2nd response 406.0 degrees fahrenheit 1st response

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Features Provided:

Bonnet packing

Valve Size:

2.000 inches

Maximum Operating Pressure:

150.0 pounds per square inch 1st response 225.0 pounds per square inch 2nd response

Outside Diameter:

6.000 inches all ends

Thickness:

0.5000 inches all ends

First Connection Face To Centerline Distance:

3.625 inches

Bolt Hole Diameter:

0.750 inches all ends

Second Connection Face To Centerline Distance:

3.625 inches

Bolt Circle Diameter:

4.750 inches all ends

Flange Face Design:

Plain all ends

Material:

Copper alloy 922 body copper alloy 922 flow control device copper alloy 922 seat copper alloy stem

Material Specification:

Qq-c-390, alloy d4/d/ federal specification single material response body qq-c-390, alloy d4/d/ federal specification single material response flow control device qq-c-390, alloy d4/d/4 federal specification single material response seat ASTM B371, alloy as per standard single material response stem

Media For Which Designed:

Steam 1st response water-oil-gas 2nd response

Style Designator:

Angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0