

View Online at <https://aerobasegroup.com/nsn/4820-00-388-9936>

**Flow Control Device:**

Disk

**Bonnet Type:**

Outside screw-yoke

**Bonnet Attachment Method:**

Bolted

**Bolt Hole Quantity:**

4 all ends

**Maximum Operating Temp:**

150.0 degrees fahrenheit 2nd response 406.0 degrees fahrenheit 1st response

**Valve Operation Method:**

Manual

**Flange Shape:**

Round with holes all ends

**Connection Type:**

Flange all ends

**Features Provided:**

Bonnet packing

**Valve Size:**

2.000 inches

**Maximum Operating Pressure:**

150.0 pounds per square inch 1st response 225.0 pounds per square inch 2nd response

**Outside Diameter:**

6.000 inches all ends

**Thickness:**

0.5000 inches all ends

**First Connection Face To Centerline Distance:**

3.625 inches

**Bolt Hole Diameter:**

0.750 inches all ends

**Second Connection Face To Centerline Distance:**

3.625 inches

**Bolt Circle Diameter:**

4.750 inches all ends

**Flange Face Design:**

Plain all ends

**Material:**

Copper alloy 922 body copper alloy 922 flow control device copper alloy 922 seat copper alloy stem

**Material Specification:**

Qq-c-390, alloy d4/d/ federal specification single material response body qq-c-390, alloy d4/d/ federal specification single material response flow control device qq-c-390, alloy d4/d/4 federal specification single material response seat ASTM B371, alloy as per standard single material response stem

**Media For Which Designed:**

Steam 1st response water-oil-gas 2nd response

**Style Designator:**

Angle flanged ends

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0