NSN 4820-00-393-4143

Safety Relief Valve - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/4820-00-393-4143

3b 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
10.0 gallons per minute
Connection Style:
Gasket sea (boss) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal boss 1st end
Features Provided:
Bonnet packing and pressure tight outlet side
Thready Qty Per Inch (tpi):
14 1st end
Adjustable Pressure Range:
+1200.0/+1300.0 pounds per square inch
Maximum Operating Pressure:
3100.0 pounds per square inch single response
Thread Size:
0.875 inches 1st end
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Surface Treatment:
Passivate
Style Designator:
Angle
Thread Series Designator:
Unjf 1st end
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-00-393-4143

Safety Relief Valve - Page 2 of 2



Demi			

No

Fiig:

A046b0