## NSN 4820-00-393-4143

Safety Relief Valve - Page 1 of 2

**Thread Class:** 



View Online at https://aerobasegroup.com/nsn/4820-00-393-4143

| 3b 1st end                                    |
|---|
| Thread Direction:                             |
| Right-hand 1st end                            |
| Flow Control Device:                          |
| Poppet  |
| Bonnet Type:                                  |
| Inside spring                                 |
| <b>Bonnet Attachment Method:</b>              |
| Integral                                      |
| Disk Loading Method:                          |
| Spring  |
| Valve Discharge Flow Rate:                    |
| 10.0 gallons per minute                       |
| Connection Style:                             |
| Gasket sea (boss) 1st end                     |
| Valve Operation Method:                       |
| Automatic                                     |
| Connection Type:                              |
| Threaded internal boss 1st end                |
| Features Provided:                            |
| Bonnet packing and pressure tight outlet side |
| Thready Qty Per Inch (tpi):                   |
| 14 1st end                                    |
| Adjustable Pressure Range:                    |
| +1200.0/+1300.0 pounds per square inch        |
| Maximum Operating Pressure:                   |
| 3100.0 pounds per square inch single response |
| Thread Size:                                  |
| 0.875 inches 1st end                          |
| Media For Which Designed:                     |
| Fuel/oil, hydrocarbon single response         |
| Surface Treatment:                            |
| Passivate                                     |
| Style Designator:                             |
| Angle   |
| Thread Series Designator:                     |
| Unjf 1st end                                  |
| Shelf Life:                                   |
| N/a   |
| Unit Of Measure:                              |

--

## NSN 4820-00-393-4143

Safety Relief Valve - Page 2 of 2



| Demi |  |  |  |
|------|--|--|--|
|      |  |  |  |
|      |  |  |  |

No

Fiig:

A046b0