NSN 4820-00-400-6785

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-400-6785

Flow Control Device:
Poppet
Bonnet Type:
Packing retaining
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Pressed-in
Bolt Hole Quantity:
4 1st end
Width:
2.400 inches 1st end
Length:
3.765 inches 2nd end
Valve Operation Method:
Automatic
Flange Shape:
Rectangular with holes 2nd end
Connection Type:
Flange 1st end
Valve Size:
1.000 inches
Thickness:
1.125 inches 2nd end
First Connection Face To Centerline Distance:
1.375 inches
Bolt Hole Diameter:
0.532 inches 2nd end
Second Connection Face To Centerline Distance:
1.562 inches
Bolt Circle Diameter:
2.313 inches 2nd end
Center To Center Distance Between Bolt Holes Along Length:
1.625 inches 1st end
Center To Center Distance Between Bolt Holes Along Width:
1.625 inches 1st end
Flange Face Design:
Recessed straight 1st end
Recess Diameter:
1.725 inches 1st end
Recess Depth:
0.125 inches 1st end

NSN 4820-00-400-6785

Safety Relief Valve - Page 2 of 2



ate		

Steel flow control device

Style Designator:

Angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0