NSN 4820-00-400-6785

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-400-6785

low Control Device:	
Poppet	
Sonnet Type:	
Packing retaining	
Disk Loading Method:	
Spring	
Renewable Seat Ring Type:	
Pressed-in	
Solt Hole Quantity:	
1st end	
Vidth:	
.400 inches 1st end	
ength:	
.765 inches 2nd end	
alve Operation Method:	
Nutomatic	
lange Shape:	
Rectangular with holes 2nd end	
Connection Type:	
lange 1st end	
/alve Size:	
.000 inches	
hickness:	
.125 inches 2nd end	
irst Connection Face To Centerline Distance:	
.375 inches	
Bolt Hole Diameter:	
.532 inches 2nd end	
Second Connection Face To Centerline Distance:	
.562 inches	
Bolt Circle Diameter:	
.313 inches 2nd end	
Center To Center Distance Between Bolt Holes Along Length:	:
.625 inches 1st end	
Center To Center Distance Between Bolt Holes Along Width:	
.625 inches 1st end	
lange Face Design:	
Recessed straight 1st end	
Recess Diameter:	
.725 inches 1st end	

0.125 inches 1st end

NSN 4820-00-400-6785

Safety Relief Valve - Page 2 of 2

Material:

Steel flow control device

Style Designator:

Angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

