

View Online at <https://aerobasegroup.com/nsn/4820-00-400-9928>

**Thread Class:**

3a 1st end

**Thread Direction:**

Right-hand 1st end

**Flow Control Device:**

Poppet

**Disk Loading Method:**

Spring

**Maximum Operating Temp:**

280.0 degrees fahrenheit single response

**Connection Style:**

Flared (tube) 1st end

**Valve Operation Method:**

Automatic

**Connection Type:**

Threaded external tube 1st end

**Maximum Operating Pressure:**

200.0 pounds per square inch single response

**Thread Size:**

0.562 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Opening Pressure Setting:**

140.0 pounds per square inch

**Outside Diameter Tube Accommodated:**

0.375 inches 1st end

**Material:**

Aluminum alloy 2024

**Material Specification:**

Qq-225/6, alloy2024, t351 federal specification 1st material response and qq-225/6, alloy2024, t4 federal specification 2nd material response

**Media For Which Designed:**

Hydrogen 5th response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 1 military specification single treatment response

**Style Designator:**

Straight through w/baffle

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0

**Mil-std (military Standard):**

Mil-a-8625 spec.