## NSN 4820-00-401-3974

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-401-3974

Flow Control Device:
Disk
Bonnet Type:
Packing retaining
Valve Discharge Flow Rate:
58300.0 pounds per hour
Renewable Seat Ring Type:
Threaded
Bolt Hole Quantity:
9 2nd end
Valve Operation Method:
Automatic
Flange Shape:
Round with holes 2nd end
Connection Type: Flange 1st end
Features Provided:
Pressure tight outlet side
Outside Diameter:
3.688 inches 2nd end
Fhickness:
1.438 inches 1st end
Bolt Hole Diameter:
0.812 inches 2nd end
Bolt Circle Diameter:
7.125 inches 2nd end
Flange Face Design:
Plain 2nd end
Raised Face Height:
0.250 inches 1st end
Raised Face Diameter:
5.000 inches 1st end
Material:
Stainless steel stem
Style Designator:
Angle
Reference Number Differentiating Characteristics:
As differentiated by the valve discharge flow rate requirementand the raised face diameter requirement
Shelf Life:
V/a

--

## NSN 4820-00-401-3974

Safety Relief Valve - Page 2 of 2



em			

Yes - demil/mli

Fiig:

A046b0