## NSN 4820-00-402-7320

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-402-7320

Flow Control Device:
Disk
Bonnet Type:
Packing retaining
Disk Loading Method:
Weight
Valve Discharge Flow Rate:
65000.0 pounds per hour
Renewable Seat Ring Type:
Threaded or welded
Bolt Hole Quantity:
9 2nd end
Valve Operation Method:
Manual or air
Flange Shape:
Round with holes 2nd end
Connection Type:
Flange 1st end
Opening Pressure Setting:
1375.0 pounds per square inch
Outside Diameter:
9.250 inches 2nd end
Thickness:
1.063 inches 3rd end
Bolt Hole Diameter:
1.188 inches 1st end
Bolt Circle Diameter:
7.688 inches 2nd end
Flange Face Design:
Plain 2nd end
Raised Face Height:
0.250 inches 1st end
Raised Face Diameter:
4.125 inches 1st end
Material:
Steel seat
Style Designator:
Angle
Reference Number Differentiating Characteristics:
As differentiated by the valve discharge flow rate requirement
Shelf Life:
N/a

## NSN 4820-00-402-7320

Safety Relief Valve - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A046b0