NSN 4820-00-403-4354

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-403-4354

Pipe Size Accommodated:
0.500 inches 1st end
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
40.0 gallons per minute
Connection Style:
Plain, optional en (pipe) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe all ends
Mounting Facility:
Threaded fastener
Features Provided:
Bonnet packing and pressure tight outlet side
Adjustable Pressure Range:
+150.0/+3000.0 pounds per square inch
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.500 inches all ends
Opening Pressure Setting:
1500.0 pounds per square inch
Material:
Steel seat
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Style Designator:
Angle
Thread Series Designator:
Nptf all ends
Shelf Life:
N/a

NSN 4820-00-403-4354

Safety Relief Valve - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A046b0