NSN 4820-00-403-4354

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-403-4354

Pipe Size Accommodated:

0.500 inches 1st end

Thread Direction:

Right-hand all ends

Flow Control Device:

Poppet

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Threaded

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

40.0 gallons per minute

Connection Style:

Plain, optional en (pipe) all ends

Valve Operation Method:

Automatic

Connection Type:

Threaded internal pipe all ends

Mounting Facility:

Threaded fastener

Features Provided:

Bonnet packing and pressure tight outlet side

Adjustable Pressure Range:

+150.0/+3000.0 pounds per square inch

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.500 inches all ends

Opening Pressure Setting:

1500.0 pounds per square inch

Material:

Steel seat

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Style Designator:

Angle

Thread Series Designator:

Nptf all ends

Shelf Life:

N/a

NSN 4820-00-403-4354

Safety Relief Valve - Page 2 of 2

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

