## NSN 4820-00-403-4692

Safety Relief Valve - Page 1 of 2

Thread Class: 3b all ends

Thread Direction:
Right-hand all ends
Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-00-403-4692

Poppet
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
4.0 gallons per minute
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Connection Style:
Gasket sea (boss) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal boss all ends
Features Provided:
Pressure tight outlet side
Maximum Operating Pressure:
250.0 pounds per square inch single response
Thread Size:
0.437 inches all ends
Opening Pressure Setting:
200.0 pounds per square inch
Outside Diameter Tube Accommodated:
0.250 inches all ends
Material:
Steel comp 303
Material Specification:
66 federal standard single material response
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Surface Treatment:
Passivate
Style Designator:
Err-090

## NSN 4820-00-403-4692

Safety Relief Valve - Page 2 of 2



Thread S	Series	Designator:
----------	--------	-------------

Unjf all ends

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0