NSN 4820-00-405-1767

Angle Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-405-1767

| Pipe Size Accommodated: | |
|--|---------|
| 4 500 1 1 4 4 4 1 | |
| 1.500 inches 1st end | |
| Flow Control Device: | |
| Disk | |
| Bonnet Type: | |
| Outside screw-yoke | |
| Bonnet Attachment Method: | |
| Bolted | |
| Maximum Operating Temp: | |
| 775.0 degrees fahrenheit single response | |
| Valve Operation Method: | |
| Manual | |
| Connection Type: | |
| Unthreaded internal pipe 1st end | |
| Features Provided: | |
| Bonnet packing | |
| Maximum Operating Pressure: | |
| 1500.0 pounds per square inch single response | |
| Special Features: | |
| Valve size 1.500 in. | |
| Media For Which Designed: | |
| Steam single response | |
| Style Designator: | |
| Angle | |
| Test Data Document: | |
| 81349-mil-s-901 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification t | format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment | ntal |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | |
| Specification Or Standard: | |
| D composition | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| Yes - demil/mli | |
| Fiig: | |
| A046b0 | |