NSN 4820-00-406-6663

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-406-6663

Pipe Size Accommodated:
0.250 inches 2nd end
Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
225.0 degrees fahrenheit single response
Connection Style:
Plain (pipe) 2nd end
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube 1st end
Thready Qty Per Inch (tpi):
18 1st end
Adjustable Pressure Range:
+4.0/+15.0 pounds per square inch
Maximum Operating Pressure:
15.0 pounds per square inch single response
Thread Size:
0.562 inches 1st end
Seat Angle:
45.0 degrees 1st end
Outside Diameter Tube Accommodated:
0.375 inches 1st end
Material:
Steel comp 316 flow control device
Material Specification:
66 federal standard single material response flow control device
Media For Which Designed:
Water-oil-gas single response
Surface Treatment:
Anodize
Style Designator:
Angle
Thread Series Designator:

Unf 1st end

NSN 4820-00-406-6663

Safety Relief Valve - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0