

View Online at <https://aerobasegroup.com/nsn/4820-00-406-6966>

Thread Class:

3a all ends

Thread Direction:

Right-hand all ends

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Maximum Operating Temp:

275.0 degrees fahrenheit single response

Connection Style:

Flareless (tube) 2nd end

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube all ends

Adjustable Pressure Range:

+85.0/+115.0 pounds per square inch

Maximum Operating Pressure:

1500.0 pounds per square inch single response

Thread Size:

0.548 inches 2nd end

Seat Angle:

37.0 degrees 1st end

Opening Pressure Setting:

100.0 pounds per square inch

Material:

Steel comp 440c flow control device

Material Specification:

Qq-a-225/6, alloy 2024, t351 federal specification single material response seat

Media For Which Designed:

Oil, hydraulic single response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Style Designator:

Straight through note: to be used for valve bodies of separable sections.

Thread Series Designator:

Unjf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.