

View Online at <https://aerobasegroup.com/nsn/4820-00-409-6328>

Body Material:

Bronze

Body Style:

Straight thru

Furnished Items:

Union nut or tailpiece

Media For Which Designed:

Water

First End Connection Type:

Threaded internal pipe

First End Style Designator:

Plain

First End Thread Size And Series/type Designator:

0.750-14 npt

First End Thread Direction:

Right-hand

Second End Relationship With First End:

Identical

Seat Material:

Nickel copper alloy

Flow Control Device:

Disk

Flow Control Device Material:

Plastic

End Connection Quantity:

2

Renewable Seat Ring Type:

Threaded

Outlet Pressure Range:

+10.0/+35.0 pounds per square inch

Regulation Type:

Manual single stage

Manual Control Method:

Screw

Valve Loading Method:

Spring

Maximum Inlet Pressure Rating:

300.0 pounds per square inch

Filter:

Included

End Application:

Spruance class dd (963), virginai class cgn (41), ticonderoga class (47), arleigh burke class ddg, nimitz class cvn, kidd class ddg, forrestal class cv. Fire pumps.

Tempurature Rating:

180.0 degrees fahrenheit

Criticality Code Justification:

Feat

Special Features:

Weapon system essential

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A21100