NSN 4820-00-413-3326

Restrictor Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-413-3326

Thread Class:
3a all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
275.0 degrees fahrenheit single response
Connection Style:
Flareless all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube all ends
Mounting Position:
Horizontal or vertical
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.437 inches all ends
Seat Angle:
12.0 degrees all ends
Special Features:
Bulkhead thread on inlet end, restricted flow 0.64 in.Gpm at 1500 psi
Material:
Steel comp 303 flow control device
Material Specification:
Qq-s-764, type 303-cancelled federal specification single material response flow control device
Media For Which Designed:
Hydraulic fluid, phosphate-ester base single response
Style Designator:
Straight thru
Thread Series Designator:
Unjf all ends
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

Yes - demil/mli

NSN 4820-00-413-3326

Restrictor Check Valve - Page 2 of 2



Fiig:

A530b0