## NSN 4820-00-413-3399

Restrictor Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-413-3399 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 275.0 degrees fahrenheit single response **Connection Style:** Flareless all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube all ends **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.437 inches all ends Seat Angle: 12.0 degrees all ends **Special Features:** Bulkhead thread on inlet end, restricted flow 0.64 in.Gpm at 1500 psi Material: Steel comp 303 flow control device **Material Specification:** Qq-s-764, type 303-cancelled federal specification single material response flow control device Media For Which Designed: Hydraulic fluid, phosphate-ester base single response **Surface Treatment:** Enamel **Surface Treatment Specification:** Mil-c-22750 military specification single treatment response **Style Designator:** Straight thru

**Thread Series Designator:** 

Unjf all ends

Shelf Life:

N/a

## NSN 4820-00-413-3399

Restrictor Check Valve - Page 2 of 2



|  | ι | Jn | it | Of | Measure: |
|--|---|----|----|----|----------|
|--|---|----|----|----|----------|

--

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-c-22750 spec.