

View Online at <https://aerobasegroup.com/nsn/4820-00-418-4808>

**Flow Control Device:**

Disk

**Bonnet Type:**

Outside screw-yoke

**Bonnet Attachment Method:**

Bolted

**Bolt Hole Quantity:**

8 all ends

**Maximum Operating Temp:**

500.0 degrees fahrenheit single response

**Valve Operation Method:**

Manual

**Flange Shape:**

Round with holes all ends

**Connection Type:**

Flange all ends

**Features Provided:**

Bonnet packing

**Valve Size:**

4.000 inches

**Maximum Operating Pressure:**

150.0 pounds per square inch single response

**Outside Diameter:**

9.000 inches all ends

**Thickness:**

0.937 inches all ends

**First Connection Face To Centerline Distance:**

5.750 inches

**Bolt Hole Diameter:**

0.625 inches all ends

**Second Connection Face To Centerline Distance:**

5.750 inches

**Flange Face Design:**

Raised straight all ends

**Raised Face Height:**

0.062 inches all ends

**Raised Face Diameter:**

6.187 inches all ends

**Material:**

Steel comp 410 stem

**Material Specification:**

Astm a105, grade 2 assn standard single material response body

**Media For Which Designed:**

Steam single response

**Style Designator:**

Angle flanged ends

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A046b0