## NSN 4820-00-419-0455

Gate Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-419-0455

| Flange Diameter:   |
|--|
| 7.500 inches   |
| Bonnet Type:   |
| Outside screw-yoke   |
| Bonnet Attachment Method:  |
| Bolted   |
| Bolt Hole Quantity:  |
| 8  |
| Valve Operation Method:  |
| Manual   |
| Connection Type:   |
| Flange, round w/holes  |
| Valve Size:  |
| 2.500 inches   |
| Maximum Operating Pressure And Media For Which Designed:   |
| 600.0 pounds per square inch steam   |
| Stem Type:   |
| Rising   |
| Maximum Operating Tempurature And Media For Which Designed:  |
| 775.0 degrees fahrenheit steam   |
| Face To Face Distance:   |
| 13.000 inches  |
| Flange Face Design:  |
| Raised   |
| Inlet Relationship With Outlet:  |
| Identical  |
| Special Features:  |
| Non-rotating stem achieves 50 percent lower operating torque; low stem head reduces ht. And wt. Of valve   |
| Material:  |
| Steel stem   |
| Material Specification:  |
| A105, grade 2 assn standard single material response body  |
| Test Data Document:  |
| 81349-mil-s-901 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental          |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  |
| Furnished Items And Quantity:  |
| 1 handwheel  |
| Specification Or Standard:   |
| D composition  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |

--

## NSN 4820-00-419-0455

Gate Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A500a0