NSN 4820-00-419-3198

Globe Valve - Page 1 of 2

Flow Control Device:

Disk



View Online at https://aerobasegroup.com/nsn/4820-00-419-3198

Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
8 1st end
Maximum Operating Temp:
775.0 degrees fahrenheit single response
Valve Operation Method:
Manual
Flange Shape:
Round with holes 1st end
Connection Type:
Flange 1st end
Features Provided:
Bonnet packing
Valve Size:
2.000 inches
Maximum Operating Pressure:
900.0 pounds per square inch single response
Outside Diameter:
6.500 inches 1st end
Thickness:
1.000 inches 1st end
Bolt Hole Diameter:
0.750 inches 1st end
Bolt Circle Diameter:
5.000 inches 1st end
Flange Face Design:
Raised straight 1st end
Raised Face Height:
0.250 inches 1st end
Raised Face Diameter:
3.625 inches 1st end
Material:
Nickel alloy 400 body
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Err-090

NSN 4820-00-419-3198

Globe Valve - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0