NSN 4820-00-419-5838



Safety Relief Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-419-5838 **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Disk Loading Method:** Spring **Valve Discharge Flow Rate:** 1.5 cubic feet per minute **Maximum Operating Temp:** -100.0 degrees fahrenheit 1st response400.0 degrees fahrenheit 2nd response **Connection Style:** Plain (tube) 1st end **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube 1st end **Maximum Operating Pressure:** 200.0 pounds per square inch single response **Thread Size:** 0.437 inches 1st end **Opening Pressure Setting:** 65.0 pounds per square inch **Outside Diameter Tube Accommodated:** 0.250 inches 1st end **Special Features:** Furnished w/defector cap Material: Aluminum alloy 2024 body **Material Specification:** Qq-a-250/4, alloy 2024 federal specification single material response seat Media For Which Designed: Nitrogen, gaseous 5th response **Style Designator:** Straight through w/baffle **Thread Series Designator:** Unjf 1st end

N/a
Unit Of Measure:

Shelf Life:

NSN 4820-00-419-5838

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0