

View Online at <https://aerobasegroup.com/nsn/4820-00-419-6029>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Disk Loading Method:

Weight

Bolt Hole Quantity:

8 1st end

Maximum Operating Temp:

775.0 degrees fahrenheit single response

Valve Operation Method:

Manual

Flange Shape:

Round with holes 1st end

Connection Type:

Flange 1st end

Mounting Position:

Horizontal

Features Provided:

Bonnet packing

Valve Size:

2.000 inches

Maximum Operating Pressure:

900.0 pounds per square inch single response

Outside Diameter:

6.500 inches 1st end

Face To Face Distance:

11.438 inches

Thickness:

1.000 inches 1st end

Bolt Hole Diameter:

0.750 inches 1st end

Bolt Circle Diameter:

5.000 inches 1st end

Flange Face Design:

Raised straight 1st end

Raised Face Height:

0.250 inches 1st end

Raised Face Diameter:

3.625 inches 1st end

Material:

Nickel alloy 400 body

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Straight through flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A530b0