## NSN 4820-00-419-9012

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-419-9012

Pipe Size Accommodated:
1.000 inches 2nd end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
80.0 cubic feet per minute
Connection Style:
Plain, optional en (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 1st end
Features Provided:
Valve stem lock shield
Thready Qty Per Inch (tpi):
11-1/2 2nd end
Maximum Operating Pressure:
165.0 pounds per square inch single response
Thread Size:
1.000 inches 2nd end
Opening Pressure Setting:
15.0 pounds per square inch
Material:
Copper alloy
Media For Which Designed:
Gas, natural 2nd response
Style Designator:
Angle
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 4820-00-419-9012

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0