NSN 4820-00-420-5485

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-420-5485

Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Connection Style:
External seat for gasket seal (boss) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external boss 1st end
Adjustable Pressure Range:
+10.0/+30.0 pounds per square inch
Maximum Operating Pressure:
200.0 pounds per square inch single response
Thread Size:
0.437 inches 1st end
Opening Pressure Setting:
25.0 pounds per square inch
Outside Diameter Tube Accommodated:
0.250 inches 1st end
Material:
Aluminum alloy 2024 seat
Material Specification:
Qq-a-225/6, alloy 2024, t4 federal specification single material response seat
Media For Which Designed:
Ammonia, gaseous 5th response
Surface Treatment:
Anodize
Style Designator:
Straight through w/baffle
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
Unit Of Measure:
om or modulo.

--

NSN 4820-00-420-5485

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0