NSN 4820-00-421-5869

Safety Relief Valve - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/4820-00-421-5869

3a 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Diaphragm
Bonnet Type:
Packing retaining
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
15.0 cubic feet per minute
Maximum Operating Temp:
330.0 degrees fahrenheit single response
Connection Style:
External seat for gasket seal (boss) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external boss 1st end
Thready Qty Per Inch (tpi):
20 1st end
Thread Size:
0.437 inches 1st end
Opening Pressure Setting:
4500.0 pounds per square inch
Outside Diameter Tube Accommodated:
0.250 inches 1st end
Material:
Steel comp 630 seat
Media For Which Designed:
Nitrogen, gaseous 2nd response
Surface Treatment:
Paint and primer
Style Designator:
Angle
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
Unit Of Measure:

NSN 4820-00-421-5869

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0