NSN 4820-00-421-5935

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-421-5935

Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
85.0 gallons per minute
Maximum Operating Temp:
160.0 degrees fahrenheit single response
Connection Style:
Gasket sea (boss) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal boss 1st end
Thready Qty Per Inch (tpi):
18 1st end
Maximum Operating Pressure:
150.0 pounds per square inch single response
Thread Size:
0.562 inches 1st end
Outside Diameter Tube Accommodated:
0.375 inches 1st end
Material:
Aluminum alloy
Media For Which Designed:
Oil, hydraulic single response
Special Test Features:
Vibration frequency range shall be 5 to 500 hz
Style Designator:
Angle
Test Data Document:
81349-mil-std-202d standard (includes industry or association standards, individual manufactureer standards, etc.).
Thread Series Designator:
Hard Andrew I

Unjf 1st end

NSN 4820-00-421-5935

Safety Relief Valve - Page 2 of 2



-			
٠.	hΔ	Iŧ.	ife:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0