NSN 4820-00-426-2290

Globe Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-426-2290

Inread Direction:
Right-hand 2nd end
Flow Control Device:
Disk
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
6 1st end
Valve Operation Method:
Manual
Flange Shape:
Round with holes 1st end
Connection Type:
Flange 1st end
Features Provided:
Bonnet packing
Thready Qty Per Inch (tpi):
7-1/2 2nd end
Maximum Operating Pressure:
250.0 pounds per square inch single response
Thread Size:
2.500 inches 2nd end
Criticality Code Justification:
Zzzy
Outside Diameter:
6.125 inches 1st end
Thickness:
0.938 inches 1st end
Bolt Hole Diameter:
0.688 inches 1st end
Bolt Circle Diameter:
5.000 inches 1st end
Flange Face Design:
Plain 1st end
Material:
Nickel alloy 400
Media For Which Designed:
Water, salt single response
Style Designator:
Straight thru

NSN 4820-00-426-2290

Globe Valve - Page 2 of 2



	Thread	Series	Design	ator:
--	--------	---------------	--------	-------

Nh 2nd end

Reference Number Differentiating Characteristics:

Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A046b0