

View Online at <https://aerobasegroup.com/nsn/4820-00-428-3097>

Thread Direction:

Right-hand all ends

Flow Control Device:

Needle

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Threaded

Maximum Operating Temp:

150.0 degrees fahrenheit single response

Connection Style:

Plain, optional en (pipe) all ends

Valve Operation Method:

Manual

Connection Type:

Threaded internal pipe all ends

Features Provided:

Bonnet packing

Thready Qty Per Inch (tpi):

18 1st end

Maximum Operating Pressure:

5000.0 pounds per square inch single response

Thread Size:

0.375 inches all ends

Material:

Steel comp 416 stem

Material Specification:

Aisi 416 assn standard single material response stem

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Straight thru

Supplementary Features:

This item has been reviewed for asbestos material. The current approved source, 36346, has indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

Thread Series Designator:

Npt all ends

Reference Number Differentiating Characteristics:

Differentiated by end connections

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0