NSN 4820-00-431-3992

Restrictor Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-431-3992

Thread Class:
3a all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
275.0 degrees fahrenheit single response
Connection Style:
Flareless all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube all ends
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
20 1st end
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.437 inches all ends
Seat Angle:
12.0 degrees all ends
Special Features:
With filter
Material:
Stainless steel flow control device
Material Specification:
Qq-a-225/6 federal specification single material response seat
Media For Which Designed:
Hydraulic fluid, mineral base single response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 2 military specification single treatment response
Style Designator:
Straight thru
Thread Series Designator:
Unjf all ends

NSN 4820-00-431-3992

Restrictor Check Valve - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.

