Stop-check Valve - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4820-00-432-1670



Pipe Size Accommodated:

1.250 inches all ends

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Maximum Operating Temp:

775.0 degrees fahrenheit single response

Connection Style:

Socket (pipe) all ends

Valve Operation Method:

Manual

Connection Type:

Unthreaded internal pipe all ends

Mounting Position:

Horizontal or vertical

Features Provided:

Bonnet packing

Maximum Operating Pressure:

600.0 pounds per square inch single response

Special Features:

Valve size 1.250 in.

Material:

Stainless steel stem

Material Specification:

Astm a105, grade 2 assn standard single material response body

Media For Which Designed:

Steam single response

Style Designator:

Angle

Test Data Document:

81349-mil-s-901 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Or Standard:

D composition

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 4820-00-432-1670

Stop-check Valve - Page 2 of 2

Fiig: A530b0

