## NSN 4820-00-432-1670

Stop-check Valve - Page 1 of 2



| view Online at https://aerobasegroup.com/nsn/4820-00-432-1670   |
|---|
| Pipe Size Accommodated:   |
| 1.250 inches all ends   |
| Flow Control Device:  |
| Disk  |
| Bonnet Type:  |
| Outside screw-yoke  |
| Bonnet Attachment Method:   |
| Bolted  |
| Maximum Operating Temp:   |
| 775.0 degrees fahrenheit single response  |
| Connection Style:   |
| Socket (pipe) all ends  |
| Valve Operation Method:   |
| Manual  |
| Connection Type:  |
| Unthreaded internal pipe all ends   |
| Mounting Position:  |
| Horizontal or vertical  |
| Features Provided:  |
| Bonnet packing  |
| Maximum Operating Pressure:   |
| 600.0 pounds per square inch single response  |
| Special Features:   |
| Valve size 1.250 in.  |
| Material:   |
| Stainless steel stem  |
| Material Specification:   |
| Astm a105, grade 2 assn standard single material response body  |
| Media For Which Designed:   |
| Steam single response   |
| Style Designator:   |
| Angle   |
| Test Data Document:   |
| 81349-mil-s-901 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental         |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.).   |
| Specification Or Standard:  |
| D composition   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |

No

## NSN 4820-00-432-1670

Stop-check Valve - Page 2 of 2



Fiig:

A530b0