NSN 4820-00-432-1671



Stop-check Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-432-1671 **Pipe Size Accommodated:** 1.000 inches all ends Flow Control Device: Disk **Bonnet Type:** Outside screw-yoke **Bonnet Attachment Method: Bolted Maximum Operating Temp:** 775.0 degrees fahrenheit single response **Connection Style:** Socket (pipe) all ends **Valve Operation Method:** Manual **Connection Type:** Unthreaded internal pipe all ends **Mounting Position:** Horizontal or vertical **Features Provided:** Bonnet packing **Maximum Operating Pressure:** 600.0 pounds per square inch single response Material: Steel seat **Material Specification:** Mil-r-17131, mil-rcocr-a military specification single material response stem Media For Which Designed: Steam single response Style Designator: Angle **Test Data Document:** 81349-mil-s-901 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Or Standard:** D composition Shelf Life: N/a

Fiig: A530b0

No

Unit Of Measure:

Demilitarization:

NSN 4820-00-432-1671

Stop-check Valve - Page 2 of 2



Mil-std (military Standard):

Mil-r-17131 spec.