## NSN 4820-00-434-6549

Expansion Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-434-6549

Pedu Material:
Body Material:
Brass
Body Style:
Angle give "adqm" or "adqn" if flanged one or two ends
Stem Material:
Steel, corrosion resisting
Furnished Items:
Nut
Media For Which Designed:
Refrigerant 22
First End Connection Type:
Unthreaded internal tube
First End Style Designator:
Socket
First End Outside Diameter Tube Accommodated:
0.500 inches
Second End Relationship With First End:
Not identical
Second End Connection Type:
Unthreaded internal tube
Second End Style Designator:
Socket
Socket Second End Outside Diameter Tube Accommodated:
Second End Outside Diameter Tube Accommodated:
Second End Outside Diameter Tube Accommodated: 0.375 inches
Second End Outside Diameter Tube Accommodated: 0.375 inches Seat Material:
Second End Outside Diameter Tube Accommodated: 0.375 inches Seat Material: Steel, corrosion resisting
Second End Outside Diameter Tube Accommodated: 0.375 inches Seat Material: Steel, corrosion resisting Flow Control Device:
Second End Outside Diameter Tube Accommodated: 0.375 inches Seat Material: Steel, corrosion resisting Flow Control Device: Stem and integral disk
Second End Outside Diameter Tube Accommodated: 0.375 inches Seat Material: Steel, corrosion resisting Flow Control Device: Stem and integral disk Flow Control Device Material:
Second End Outside Diameter Tube Accommodated: 0.375 inches Seat Material: Steel, corrosion resisting Flow Control Device: Stem and integral disk Flow Control Device Material: Steel, corrosion resisting
Second End Outside Diameter Tube Accommodated: 0.375 inches Seat Material: Steel, corrosion resisting Flow Control Device: Stem and integral disk Flow Control Device Material: Steel, corrosion resisting End Connection Quantity:
Second End Outside Diameter Tube Accommodated: 0.375 inches Seat Material: Steel, corrosion resisting Flow Control Device: Stem and integral disk Flow Control Device Material: Steel, corrosion resisting End Connection Quantity: 2
Second End Outside Diameter Tube Accommodated: 0.375 inches Seat Material: Steel, corrosion resisting Flow Control Device: Stem and integral disk Flow Control Device Material: Steel, corrosion resisting End Connection Quantity: 2 Capillary Tube Length:
Second End Outside Diameter Tube Accommodated: 0.375 inches Seat Material: Steel, corrosion resisting Flow Control Device: Stem and integral disk Flow Control Device Material: Steel, corrosion resisting End Connection Quantity: 2 Capillary Tube Length: 36.000 inches
Second End Outside Diameter Tube Accommodated: 0.375 inches Seat Material: Steel, corrosion resisting Flow Control Device: Stem and integral disk Flow Control Device Material: Steel, corrosion resisting End Connection Quantity: 2 Capillary Tube Length: 36.000 inches Bulb Length:
Second End Outside Diameter Tube Accommodated: 0.375 inches Seat Material: Steel, corrosion resisting Flow Control Device: Stem and integral disk Flow Control Device Material: Steel, corrosion resisting End Connection Quantity: 2 Capillary Tube Length: 36.000 inches Bulb Length: 2.094 inches
Second End Outside Diameter Tube Accommodated: 0.375 inches Seat Material: Steel, corrosion resisting Flow Control Device: Stem and integral disk Flow Control Device Material: Steel, corrosion resisting End Connection Quantity: 2 Capillary Tube Length: 36.000 inches Bulb Length: 2.094 inches Bulb Diameter: 0.500 inches
Second End Outside Diameter Tube Accommodated: 0.375 inches Seat Material: Steel, corrosion resisting Flow Control Device: Stem and integral disk Flow Control Device Material: Steel, corrosion resisting End Connection Quantity: 2 Capillary Tube Length: 36.000 inches Bulb Length: 2.094 inches
Second End Outside Diameter Tube Accommodated: 0.375 inches Seat Material: Steel, corrosion resisting Flow Control Device: Stem and integral disk Flow Control Device Material: Steel, corrosion resisting End Connection Quantity: 2 Capillary Tube Length: 36.000 inches Bulb Length: 2.094 inches Bulb Diameter: 0.500 inches Valve Expansion Control Type: Thermostatic
Second End Outside Diameter Tube Accommodated: 0.375 inches Seat Material: Steel, corrosion resisting Flow Control Device: Stem and integral disk Flow Control Device Material: Steel, corrosion resisting End Connection Quantity: 2 Capillary Tube Length: 36.000 inches Bulb Length: 2.094 inches Bulb Diameter: 0.500 inches

## NSN 4820-00-434-6549

Expansion Valve - Page 2 of 2



Valve Pressure Limiting Device: Not included Bulb Media Type: Refrigerant 22 Bulb Mounting Method: Clamp Valve Equalizer Location: External Valve Equalizer Connection Type: Solder tube Valve Equalizer Connection Diameter: 0.250 inches **Refrigeration Capacity In Btu Per Hour:** 36.0 **Special Features:** Bolts 2, nuts 2 also furnished Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A07100