NSN 4820-00-438-3962

Lift-check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-438-3962

Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Disk Loading Method:
Spring
Maximum Operating Temp:
165.0 degrees fahrenheit single response
Connection Style:
Flare (tube) 1st end
Valve Operation Method:
Manual
Connection Type:
Threaded internal tube 1st end
Mounting Facility:
Threaded fastener
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
18 1st end
Maximum Operating Pressure:
1500.0 pounds per square inch single response
Thread Size:
0.562 inches 1st end
Face To Face Distance:
3.531 inches
Outside Diameter Tube Accommodated:
0.375 inches 1st end
Special Features:
Handle turns 90 degrees ccw to open position
Material:
Steel stem
Media For Which Designed:
Oil, hydraulic single response
Surface Treatment:
Anodize
Style Designator:
Straight thru
Supplementary Features:
Optional flow control device: stem
Thread Series Designator:
Unf 1st end

NSN 4820-00-438-3962

Lift-check Valve - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0