

View Online at <https://aerobasegroup.com/nsn/4820-00-438-8462>

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Maximum Operating Temp:

180.0 degrees fahrenheit single response

Connection Style:

Flareless 2nd end

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube 2nd end

Mounting Position:

Horizontal or vertical

Thready Qty Per Inch (tpi):

24 2nd end

Maximum Operating Pressure:

600.0 pounds per square inch single response

Thread Size:

0.375 inches 1st end

Seat Angle:

37.0 degrees 1st end

Outside Diameter Tube Accommodated:

0.188 inches 2nd end

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-225/6, alloy 2024, t4 federal specification single material response

Media For Which Designed:

Fuel/oil, hydrocarbon 2nd response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response

Style Designator:

Straight thru

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.