## NSN 4820-00-438-9064

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-438-9064

View Online at https://aerobasegroup.com/nsn/4820-00-438-906
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
2.5 gallons per minute
Maximum Operating Temp:
160.0 degrees fahrenheit single response
Connection Style:
Gasket sea (boss) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal boss 1st end
Thready Qty Per Inch (tpi):
18 1st end
Adjustable Pressure Range:
+1000.0 to 3000.0 pounds per square inch
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.562 inches 1st end
Opening Pressure Setting:
1000.0 pounds per square inch
Material:
Steel seat
Material Specification:
Qq-a-250/4 federal specification single material response body
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Style Designator:
Err-090
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
Unit Of Measure:

---

## NSN 4820-00-438-9064

Safety Relief Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-s-5002 spec.

