## NSN 4820-00-444-2622

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-444-2622

Flow Control Device:
Disk
Bolt Hole Quantity:
4 2nd end
Maximum Operating Temp:
160.0 degrees fahrenheit single response
Width:
3.000 inches 2nd end
Length:
3.000 inches 2nd end
Valve Operation Method:
Automatic or manual
Flange Shape:
Rectangular with holes 2nd end
Connection Type:
Flange all ends
Mounting Position:
Horizontal or vertical
Maximum Operating Pressure:
60.0 pounds per square inch single response
Outside Diameter:
3.875 inches 1st end
Thickness:
0.250 inches all ends
Bolt Hole Diameter:
0.328 inches 2nd end
Bolt Circle Diameter:
3.125 inches 1st end
Center To Center Distance Between Bolt Holes Along Length:
2.375 inches 2nd end
Center To Center Distance Between Bolt Holes Along Width:
2.375 inches 2nd end
Flange Face Design:
Plain all ends
Material:
Aluminum alloy
Material Specification:
Qq-a-601 federal specification single material response
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Surface Treatment:
Anodize

## NSN 4820-00-444-2622

Check Valve - Page 2 of 2



Surface Treatment S	pecification:
---------------------	---------------

Mil-a-8625 military specification single treatment response

**Style Designator:** 

Straight through flanged ends

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.