

View Online at <https://aerobasegroup.com/nsn/4820-00-446-3236>

**Thread Class:**

2a 2nd end

**Thread Direction:**

Right-hand 2nd end

**Flow Control Device:**

Disk

**Bonnet Type:**

Inside screw

**Bonnet Attachment Method:**

Bolted

**Connection Style:**

Flared (tube) 2nd end

**Valve Operation Method:**

Manual

**Connection Type:**

Unthreaded internal tube 1st end

**Features Provided:**

Bonnet packing

**Thready Qty Per Inch (tpi):**

26 2nd end

**Maximum Operating Pressure:**

300.0 pounds per square inch single response

**Thread Size:**

0.750 inches 2nd end

**Seat Angle:**

45.0 degrees 2nd end

**Outside Diameter Tube Accommodated:**

0.500 inches 2nd end

**Material:**

Lead flow control device

**Media For Which Designed:**

Refrigerant 12 single response

**Style Designator:**

Angle

**Test Data Document:**

81349-mil-v-22064 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unf 2nd end

**Furnished Items And Quantity:**

1 cap and 1 chain

**Specification Or Standard:**

lil type and 8 class

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0