## NSN 4820-00-446-3311

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-446-3311

Pipe Size Accommodated:
0.750 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Connection Style:
Plain (pipe) 1st end
Valve Operation Method:
Automatic or manual
Connection Type:
Threaded external pipe 1st end
Adjustable Pressure Range:
+105.0/+115.0 pounds per square inch
Maximum Operating Pressure:
Maximum Operating Pressure: 250.0 pounds per square inch single response
250.0 pounds per square inch single response
250.0 pounds per square inch single response  Thread Size:
250.0 pounds per square inch single response  Thread Size:  0.750 inches 1st end
250.0 pounds per square inch single response  Thread Size: 0.750 inches 1st end  Material:
250.0 pounds per square inch single response  Thread Size: 0.750 inches 1st end  Material:  Copper alloy
250.0 pounds per square inch single response  Thread Size: 0.750 inches 1st end  Material:  Copper alloy  Media For Which Designed:
250.0 pounds per square inch single response  Thread Size: 0.750 inches 1st end  Material: Copper alloy  Media For Which Designed: Fuel/oil, hydrocarbon 2nd response
250.0 pounds per square inch single response  Thread Size: 0.750 inches 1st end  Material: Copper alloy  Media For Which Designed: Fuel/oil, hydrocarbon 2nd response  Style Designator:
250.0 pounds per square inch single response  Thread Size: 0.750 inches 1st end  Material: Copper alloy  Media For Which Designed: Fuel/oil, hydrocarbon 2nd response  Style Designator: Straight thru
250.0 pounds per square inch single response Thread Size: 0.750 inches 1st end Material: Copper alloy Media For Which Designed: Fuel/oil, hydrocarbon 2nd response Style Designator: Straight thru Thread Series Designator:
250.0 pounds per square inch single response Thread Size: 0.750 inches 1st end Material: Copper alloy Media For Which Designed: Fuel/oil, hydrocarbon 2nd response Style Designator: Straight thru Thread Series Designator: Npt 1st end
250.0 pounds per square inch single response Thread Size: 0.750 inches 1st end Material: Copper alloy Media For Which Designed: Fuel/oil, hydrocarbon 2nd response Style Designator: Straight thru Thread Series Designator: Npt 1st end Shelf Life:
250.0 pounds per square inch single response Thread Size: 0.750 inches 1st end Material: Copper alloy Media For Which Designed: Fuel/oil, hydrocarbon 2nd response Style Designator: Straight thru Thread Series Designator: Npt 1st end Shelf Life: N/a
250.0 pounds per square inch single response Thread Size: 0.750 inches 1st end Material: Copper alloy Media For Which Designed: Fuel/oil, hydrocarbon 2nd response Style Designator: Straight thru Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure:
250.0 pounds per square inch single response Thread Size: 0.750 inches 1st end Material: Copper alloy Media For Which Designed: Fuel/oil, hydrocarbon 2nd response Style Designator: Straight thru Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure:
250.0 pounds per square inch single response Thread Size: 0.750 inches 1st end Material: Copper alloy Media For Which Designed: Fuel/oil, hydrocarbon 2nd response Style Designator: Straight thru Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: