NSN 4820-00-449-3518

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-449-3518

Pipe Size Accommodated:
0.250 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
40.5 cubic feet per minute
Maximum Operating Temp:
60.0 degrees fahrenheit single response
Connection Style:
Plain (pipe) 1st end
Valve Operation Method:
Automatic or manual
Connection Type:
Threaded external pipe 1st end
Features Provided:
Valve stem lock shield
Thready Qty Per Inch (tpi):
18 1st end
Maximum Operating Pressure:
70.0 pounds per square inch single response
Thread Size:
0.250 inches 1st end
Opening Pressure Setting:
70.0 pounds per square inch
Material:
Copper alloy body
Media For Which Designed:
Air single response
Style Designator:
Err-090
Thread Series Designator:
Npt 1st end
Reference Number Differentiating Characteristics:
As differentiated by pressure setting data and valve size
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-00-449-3518

Safety Relief Valve - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A046b0