NSN 4820-00-449-4527

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-449-4527 **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: Piston **Bonnet Type:** Inside spring **Bonnet Attachment Method:** Threaded **Maximum Operating Temp:** 225.0 degrees fahrenheit single response **Connection Style:** Flared (tube) 1st end **Connection Type:** Threaded external tube 2nd end **Features Provided:** Bonnet packing and pressure tight outlet side Thready Qty Per Inch (tpi): 16 1st end **Adjustable Pressure Range:** +115.0/+250.0 pounds per square inch **Maximum Operating Pressure:** 250.0 pounds per square inch single response **Thread Size:** 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end **Opening Pressure Setting:** 200.0 pounds per square inch **Outside Diameter Tube Accommodated:** 0.500 inches 1st end Material: Stainless steel flow control device **Material Specification:** Qq-a-225/4 federal specification single material response seat **Surface Treatment:** Anodize **Style Designator:**

Angle

Thread Series Designator:

Unf 1st end

NSN 4820-00-449-4527

Safety Relief Valve - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0