NSN 4820-00-450-6539

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-450-6539

| Thread Class: |
|---|
| 3a 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Flow Control Device: |
| Poppet |
| Disk Loading Method: |
| Spring |
| Connection Style: |
| Flared (tube) 1st end |
| Valve Operation Method: |
| Automatic |
| Connection Type: |
| Threaded external tube 1st end |
| Thready Qty Per Inch (tpi): |
| 20 1st end |
| Thread Size: |
| 0.437 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Opening Pressure Setting: |
| 1425.0 pounds per square inch |
| Outside Diameter Tube Accommodated: |
| 0.250 inches 1st end |
| Material: |
| Aluminum alloy seat |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-a-8625 military specification single treatment response |
| Style Designator: |
| Angle |
| Thread Series Designator: |
| Unf 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A046b0

NSN 4820-00-450-6539

Safety Relief Valve - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.