## NSN 4820-00-451-0646

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-451-0646 **Thread Class:** 3b all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Bonnet Type:** Inside spring **Bonnet Attachment Method:** Threaded **Disk Loading Method:** Spring **Maximum Operating Temp:** 180.0 degrees fahrenheit single response **Connection Style:** Gasket sea (boss) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss all ends **Features Provided:** Bonnet packing and pressure tight outlet side **Adjustable Pressure Range:** +115.0/+250.0 pounds per square inch **Maximum Operating Pressure:** 3100.0 pounds per square inch single response **Thread Size:** 0.437 inches all ends **Opening Pressure Setting:** 200.0 pounds per square inch **Outside Diameter Tube Accommodated:** 0.250 inches all ends Material: Aluminum alloy Media For Which Designed: Oil, hydraulic 2nd response **Surface Treatment:** Anodize Style Designator: Angle **Thread Series Designator:** 

Unjf all ends

## NSN 4820-00-451-0646

Safety Relief Valve - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0