NSN 4820-00-454-1087

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-454-1087

| Pipe Size Accommodated: |
|-------------------------------------|
| 0.500 inches 2nd end |
| Thread Class: |
| 3a 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Flow Control Device: |
| Disk |
| Bonnet Type: |
| Inside screw |
| Bonnet Attachment Method: |
| Integral |
| Disk Loading Method: |
| Spring |
| Valve Discharge Flow Rate: |
| 302.0 cubic feet per minute |
| Connection Style: |
| Plain (pipe) 2nd end |
| Valve Operation Method: |
| Automatic |
| Connection Type: |
| Threaded external tube 1st end |
| Thread Size: |
| 0.875 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Opening Pressure Setting: |
| 300.0 pounds per square inch |
| Outside Diameter Tube Accommodated: |
| 0.625 inches 1st end |
| Material: |
| Stainless steel seat |
| Style Designator: |
| Angle |
| Thread Series Designator: |
| Unf 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

NSN 4820-00-454-1087

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0