## NSN 4820-00-454-1087

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-454-1087

| Pipe Size Accommodated:             |
|-------------------------------------|
| 0.500 inches 2nd end                |
| Thread Class:                       |
| 3a 1st end                          |
| Thread Direction:                   |
| Right-hand 1st end                  |
| Flow Control Device:                |
| Disk                                |
| Bonnet Type:                        |
| Inside screw                        |
| <b>Bonnet Attachment Method:</b>    |
| Integral                            |
| Disk Loading Method:                |
| Spring                              |
| Valve Discharge Flow Rate:          |
| 302.0 cubic feet per minute         |
| Connection Style:                   |
| Plain (pipe) 2nd end                |
| Valve Operation Method:             |
| Automatic                           |
| Connection Type:                    |
| Threaded external tube 1st end      |
| Thread Size:                        |
| 0.875 inches 1st end                |
| Seat Angle:                         |
| 37.0 degrees 1st end                |
| Opening Pressure Setting:           |
| 300.0 pounds per square inch        |
| Outside Diameter Tube Accommodated: |
| 0.625 inches 1st end                |
| Material:                           |
| Stainless steel seat                |
| Style Designator:                   |
| Angle                               |
| Thread Series Designator:           |
| Unf 1st end                         |
| Shelf Life:                         |
| N/a                                 |
| Unit Of Measure:                    |
|                                     |
| Demilitarization:                   |
| No                                  |

## NSN 4820-00-454-1087

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0